


PIN OUT



SHELL ———— SHELL

REQUIREMENTS:

1:100% short and open testing.

2:Test conditions

DC300V /10MS

Insulation resistance 10MΩ(Min)

Conduction resistance 5Ω(Max)

| | | | | |
|-----|--------------|---|-------|------|
| ⑤ | OUTER MOLDED | BLACK 45P PVC | 0.021 | KG |
| ④ | INTER MOLDED | LDPE | 0.008 | KG |
| ③ | CONNECTOR | USB A TYPE FEMALE,WHITE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN | 1 | PCS |
| ② | CONNECTOR | USB A TYPE MALE,WHITE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN | 1 | PCS |
| ① | CABLE | USB2.0 28#*1P+28#*2C+ADB OD:3.9±0.1 JACKET:BLACK PVC | 1.5 | M |
| NO. | MATERIAL | DESCRIPTIONG | QTY. | UNIT |

| Ltemref | Quantity | Title/Name,designation,material,dimension etc | | | Article No./Reference | |
|-------------|------------|---|--------------------|--------------|-----------------------|--|
| Designed by | Checked by | Approved by - date | File name | Date | Scale | |
| | | MARCH 4.2012 | USB AM TO AF L=15M | MARCH 4.2012 | FREE | |
| | | | 26-2803 | | | |
| | | | 26-2803 | Edition 1 | Sheet 1/2 | |